



magnaloy coupling company Pump/Motor Mounts

Power unit design and assembly can be greatly simplified by use of **Magnaloy Pump/Motor Mounts**. Direct mounting of flange-mount pumps to NEMA C face motors via pump/motor mounts eliminates the need for a coupling guard, foot brackets, shims, risers and a mounting plate. The result is the easiest to install, most cost effective method available to mount a pump and motor. Both horizontal and vertical styles are available. For a complete catalog, or application assistance, contact your local **Womack** sales professional.



Magnaloy Pump/Motor Mounts are cast of a lightweight high strength aluminum alloy and incorporate many unique design features. Custom molded OSHA Orange coupling access covers are included with all mounts for NEMA frames 182 and larger. Most **Magnaloy** mounts are supplied with a pre-cast drain hole for residual fluids. This aids in quicker detection of leaky seals and other trouble areas.

Horizontal Mount Pump/Motor Mounts

PART NUMBER	PUMP FLANGE	MOTOR FRAME	LENGTH (inches)
M056422A (4A)	SAE A, 2(4)BOLT	56C/143TC/145TC	4.2
M056452A (4A)	SAE A, 2(4)BOLT	56C/143TC/145TC	4.5
M056502A (4A)	SAE A, 2(4)BOLT	56C/143TC/145TC	5.0
M056522A (4A)	SAE A, 2(4)BOLT	56C/143TC/145TC	5.2
M056522B (4B)	SAE B, 2(4)BOLT	56C/143TC/145TC	5.2
M182502A (4A)	SAE A, 2(4)BOLT	182TC/184TC/213TC 215TC/254TC/256TC	5.0
M182522A (4A)	SAE A, 2(4)BOLT	182TC/184TC/213TC 215TC/254TC/256TC	5.2
M182522B (4B)	SAE B, 2(4)BOLT	182TC/184TC/213TC 215TC/254TC/256TC	5.2
M182582A (4A)	SAE A, 2(4)BOLT	182TC/184TC/213TC 215TC/254TC/256TC	5.8
M182582B (4B)	SAE B, 2(4)BOLT	182TC/184TC/213TC 215TC/254TC/256TC	5.8
M182602B (4B)	SAE B, 2(4)BOLT	182TC/184TC/213TC 215TC/254TC/256TC	6.0
M182682A (4A)	SAE A, 2(4)BOLT	182TC/184TC/213TC 215TC/254TC/256TC	6.8
M182682B (4B)	SAE B, 2(4)BOLT	182TC/184TC/213TC 215TC/254TC/256TC	6.8
M182682C (4C)	SAE C, 2(4)BOLT	182TC/184TC/213TC 215TC/254TC/256TC	6.8
M182702B (4B)	SAE B, 2(4)BOLT	182TC/184TC/213TC 215TC/254TC/256TC	7.0
M182702C (4B)	SAE C, 2(4)BOLT	182TC/184TC/213TC 215TC/254TC/256TC	7.0
M284752C (4C)	SAE C, 2(4)BOLT	284TC/286TC/284TSC 286TSC	7.5
M324762C (4C)	SAE C, 2(4)BOLT	284TC/286TC/284TSC 286TSC	7.6

This is not a complete part number listing, these are the most popular sizes used. For a complete catalog, or application assistance, contact your local **Womack** sales professional.